



# MACHINE ROOF BELLOW COVERS

**LIGHTWEIGHT, MOVABLE FOLDING COVER FOR MACHINE TOOLS**

Protect against dust, particles, and other debris from escaping or entering the roof of the machine tool

## TECHNICAL DETAILS

- 2 ply, rigid polyester (PET) sheets with polyurethane (TPU) coating on both sides (1 mm thick)
- Temperature resistance -20°C (-4°F) to 100°C (212°F)
- Width up to 8,000 mm
- Standard fold depth 125 mm (up to 330 mm)
- Speed up to 90 m/min
- Acceleration up to 1g
- Transverse beams made of aluminum hollow profile
- White, translucent fold material provides an optimum brightness in the working area
- Motorized version for opening and closing
- Individual folding segments are replaceable
- Decoupling option for crane loading and unloading
- Material for special applications available upon request
- Implementation can be completed with a pre-existing or new/customized slide way
- Slide way systems depending on requirements (rollers, gliders, slide ways)



**ISO 9001:2015  
REGISTERED**

# QUOTE REQUEST (ROOF BELLOWS)

Please complete this form and email to [info@hennig-inc.com](mailto:info@hennig-inc.com).

## COMPANY

Company Name \_\_\_\_\_  
Company Address \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Name \_\_\_\_\_  
Title \_\_\_\_\_  
E-mail \_\_\_\_\_  
Phone \_\_\_\_\_ Fax \_\_\_\_\_

## APPLICATION / ENVIRONMENT

Quantity \_\_\_\_\_

Protection For ☐ Dust/Particle Containment ☐ Noise Attenuation ☐ Other (provide description below) \_\_\_\_\_

Mounting ☐ Existing rails (provide dimensions) \_\_\_\_\_ ☐ inch ☐ mm  
☐ Hennig to supply rails

Machine Speed \_\_\_\_\_ Acceleration \_\_\_\_\_ (provide unit of measurement for each value)

Machine Width \_\_\_\_\_ ☐ inch ☐ mm Machine Length \_\_\_\_\_ ☐ inch ☐ mm

Notes \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

## DIMENSIONS/TRAVEL

UOM ☐ inch ☐ mm

Extended Length \_\_\_\_\_ Retracted Length \_\_\_\_\_ Travel Length \_\_\_\_\_

