


The background of the advertisement features a dark blue gradient with several technical drawings of wiper systems. On the left, there are two circular wiper components, one above the other, showing internal profiles. On the right, there are three rectangular wiper components, one standing vertically and two lying horizontally at the bottom right. The Hennig logo is in the top left corner.

||| HENNIG®

WIPER SYSTEMS

MOLDED | ALUMINUM ENCASED | STEEL ENCASED | TELESCOPIC STEEL WAY COVER WIPERS



Safe processes are profitable processes. We make our customers successful by protecting people and machines from the manufacturing environment and waste.

AT HENNIG, YOUR **SUCCESS** ALWAYS COMES FIRST.

Hennig Worldwide has been a global leader since 1950, specializing in chip and coolant management, machine protection, and facility safety. We work with a wide variety of manufacturers and other facilities worldwide, helping them create and maintain safe and efficient workplaces. Our commitment to excellence extends beyond our services—we actively contribute to local communities, create regional jobs, and support the global needs of machine tool customers.

TABLE OF CONTENTS

4	Overview & Types
5-13	Molded Wipers (HEMW, SK)
14	Aluminum Encased Wipers(AL)
15	Steel Encased Wipers (AB)
16-17	Telescopic Steel Way Cover Wipers (C-Series, CL1, eN, F)
18-19	Facilities & Contacts






PROTECT YOUR SUCCESS

The huge field of applications in the machine tool sector has, over the years, created an increasing number of unique, specialized wipers as well as a large number of sealing solutions. Whether you require resistance to abrasion, chips, oils, coolants, acids, greases, high temperatures, or low coefficient and friction on guideways, we have wipers and sealant systems for any of your requirements. In addition to a wide range of stock wipers, we can also manufacture extremely durable custom wipers for your application.

OVERVIEW & TYPES


- Wide range of stock wipers
- Any custom shapes according to your requirements
- Excellent durability
- Various material choices for resistance to oils, greases, coolants, chips, and high temperatures



MOLDED WIPERS

- Over 20 standard designs for a variety of applications
- NBR and FPM wiper lips with steel, aluminum, or no insert (depending on wiper type)
- Custom molds and special materials available depending on your application


See pages 6-13 for details



ALUMINUM ENCASED WIPERS

- Polyurethane 85 shore A wiper lip with aluminum carrier
- Low weight
- Low coefficient of friction


See page 14 for details



STAINLESS STEEL ENCASED WIPERS

- Polyurethane wiper lip with stainless steel carrier
- Sealing on backside to prevent coolant flow
- High mechanical load capacity

See page 15 for details




TELESCOPING COVER & APRON COVER WIPERS

- Polyurethane wiper lip with steel carrier
- Designed with a low profile specifically for telescopic steel covers and apron covers
- Replaceable wiper lips


See pages 16-17 for details

MOLDED WIPERS


- A new generation of wipers - custom molded per your requirements
- NBR and FPM wiper lips with steel, aluminum, or no insert (depending on wiper type)
- Excellent resistance to abrasion, chemicals, coolants, mineral oils, and acids
- Low sliding friction
- Over 20 standard designs for a variety of applications
- Custom molds and special materials available depending on your application



HEMW A
page 7




HEMW B
page 7



HEMW C
page 8



HEMW CS
page 8




HEMW D
page 8




HEMW E
page 9



HEMW F
page 9




HEMW G
page 9




HEMW H
page 9




HEMW L
page 10



HEMW R
page 10



HEMW V
page 10




HEMW K
page 10




HEMW P
page 11




HEMW S
page 11




HEMW N
page 11




HEMW U 1-2
page 11




HEMW U 3-4
page 12



HEMW U 5-6
page 12



HEMW U 7-8
page 12



HEMW U 9-10
page 12



HEMW U 11-12
page 13



HEMW X 1-2
page 13



HEMW X 3-4
page 13




SK
page 13

MOLDED WIPERS

All dimensions shown in mm.

HEMW A

Type	H	T	Length	Material
HEMW A1	14	6.5	500	NBR
HEMW A2	14	6.5	500	FPM
HEMW A3	18	6.5	500	NBR
HEMW A4	18	6.5	500	FPM
HEMW A5	25	6.5	500	NBR
HEMW A6	25	6.5	500	FPM
HEMW A7	14	5	500	NBR
HEMW A8	14	5	500	FPM
HEMW A9	18	5	500	NBR
HEMW A10	18	5	500	FPM
HEMW A11	25	5	500	NBR
HEMW A12	25	5	500	FPM




MOLDED WIPERS

All dimensions shown in mm.

HEMW B

Type	H	S	W	T	Length	Material
HEMW B 1	9.5	7.5	2.5	5	560	NBR
HEMW B 1 L	9.5	7.5	2.5	5	1000	NBR
HEMW B 2	9.5	7.5	2.5	5	560	FPM
HEMW B 2 L	9.5	7.5	2.5	5	1000	FPM
HEMW B 3	15	11.5	5	7	560	NBR
HEMW B 3 L	15	11.5	5	7	1000	NBR
HEMW B 4	15	11.5	5	7	560	FPM
HEMW B 4 L	15	11.5	5	7	1000	FPM
HEMW B 5	18	15	5	9	560	NBR
HEMW B 5 L	18	15	5	9	1000	NBR
HEMW B 6	18	15	5	9	560	FPM
HEMW B 6 L	18	15	5	9	1000	FPM
HEMW B 7	21	17.5	5	7	560	NBR
HEMW B 7 L	21	17.5	5	7	1000	NBR
HEMW B 8	21	17.5	5	7	560	FPM
HEMW B 8 L	21	17.5	5	7	1000	FPM
HEMW B 9	25	21	11	11	560	NBR
HEMW B 9 L	25	21	11	11	1000	NBR
HEMW B 10	25	21	11	11	560	FPM
HEMW B 10 L	25	21	11	11	1000	FPM
HEMW B 11	26	23	5	7	560	NBR
HEMW B 11 L	26	23	5	7	1000	NBR
HEMW B 12	26	23	5	7	560	FPM
HEMW B 12 L	26	23	5	7	1000	FPM
HEMW B 13	30	27	5	7	560	NBR
HEMW B 14	31	27	5	7	560	FPM
HEMW B 15	31	28	5	7	560	NBR
HEMW B 15 L	31	28	5	7	1000	NBR
HEMW B 16	31	28	5	7	560	FPM
HEMW B 16 L	31	28	5	7	1000	FPM
HEMW B 17	36	33	5	7	560	NBR
HEMW B 18	36	33	5	7	560	FPM
HEMW B 19	39	36	5	7	560	NBR
HEMW B 20	39	36	5	7	560	FPM




MOLDED WIPERS

All dimensions shown in mm.

HEMW C


Type	Protection	H	S	W	T	D	Length	Material
HEMW C 1	Spring Steel	25	15.5	3	12	29	800	NBR
HEMW C 2	Spring Steel	25	15.5	3	12	29	800	FPM
HEMW C 3	-	25	15.5	3	12	-	800	NBR
HEMW C 4	-	25	15.5	3	12	-	800	FPM
HEMW C 5	Spring Steel	30	20.5	3	12	34	800	NBR
HEMW C 5 L	Spring Steel	30	20.5	3	12	34	1000	NBR
HEMW C 6	Spring Steel	30	20.5	3	12	34	800	FPM
HEMW C 6 L	Spring Steel	30	20.5	3	12	34	1000	FPM
HEMW C 7	-	30	20.5	3	12	-	800	NBR
HEMW C 7 L	-	30	20.5	3	12	-	1000	NBR
HEMW C 8	-	30	20.5	3	12	-	800	FPM
HEMW C 8 L	-	30	20.5	3	12	-	1000	FPM
HEMW C 9	Spring Steel	35	25.5	3	12	39	800	NBR
HEMW C 10	Spring Steel	35	25.5	3	12	39	800	FPM
HEMW C 11	-	35	25.5	3	12	-	800	NBR
HEMW C 12	-	35	25.5	3	12	-	800	FPM



w/ steel spring

HEMW CS


Type	Protection	H	S	W	T	Length	Material
HEMW CS 1	Spring Steel	27	22.7	3	7.3	800	NBR
HEMW CS 2	Spring Steel	27	22.7	3	7.3	800	FPM
HEMW CS 3	-	27	22.7	3	7.3	800	NBR
HEMW CS 4	-	27	22.7	3	7.3	800	FPM
HEMW CS 5	Spring Steel	27	22.7	3	7.3	1500	NBR
HEMW CS 6	Spring Steel	27	22.7	3	7.3	1500	FPM
HEMW CS 7	-	27	22.7	3	7.3	1500	NBR
HEMW CS 8	-	27	22.7	3	7.3	1500	FPM



w/ steel spring

HEMW D

Type	Protection	H	S	W	T	Length	Material
HEMW D 1	Spring Steel	39	27	3	15	850	NBR
HEMW D 2	Spring Steel	39	27	3	15	850	FPM
HEMW D 3	-	39	27	3	15	850	NBR
HEMW D 4	-	39	27	3	15	850	FPM
HEMW D 5	Spring Steel	32	20	3	15	850	NBR
HEMW D 6	Spring Steel	32	20	3	15	850	FPM
HEMW D 7	-	32	20	3	15	850	NBR
HEMW D 8	-	32	20	3	15	850	FPM
HEMW D 9	Spring Steel	45	27	3	21.5	1000	NBR
HEMW D 10	Spring Steel	45	27	3	21.5	1000	FPM
HEMW D 11	-	45	27	3	21.5	1000	NBR
HEMW D 12	-	45	27	3	21.5	1000	FPM



MOLDED WIPERS


All dimensions shown in mm.

HEMW E

Type	Protection	H	S	W	Length	Material
HEMW E 1	Spring Steel	25	17.3	2	600	NBR
HEMW E 2	Spring Steel	25	17.3	2	600	FPM
HEMW E 3	-	34	19.3	2	600	NBR
HEMW E 4	-	34	19.3	2	600	FPM

Swinging stripping lip

Classic design with steel support




HEMW F

Type	H	T	Length	Material
HEMW F 1	22	10.5	1000	NBR
HEMW F 2	22	10.5	1000	FPM
HEMW F 3	28	10.5	1000	NBR
HEMW F 4	28	10.5	1000	FPM
HEMW F 5	40	10.5	1000	NBR
HEMW F 6	40	10.5	1000	FPM




HEMW G

Type	H	S	W	T	Length	Material
HEMW G 1	30	17	5	15.5	600	NBR
HEMW G 2	40	17	5	15.5	600	FPM
HEMW G 3	40	27	5	15.5	600	NBR
HEMW G 4	40	27	5	15.5	600	FPM



HEMW H

Type	H	S	W	T	Length	Material
HEMW H 1	12.5	11	2	6	500	NBR
HEMW H 2	12.5	11	2	6	500	FPM




MOLDED WIPERS

All dimensions shown in mm.


HEMW L

Type	H	T	Length	Material
HEMW L 1	18.5	6.5	1000	NBR
HEMW L 2	18.5	6.5	1000	FPM
HEMW L 3	22	6.5	1000	NBR
HEMW L 4	22	6.5	1000	FPM
HEMW L 5	26	6.5	1000	NBR
HEMW L 6	26	6.5	1000	FPM




HEMW R

Type	H	T	W	Length	Material
HEMW R 1	18	6.5	12	300	NBR
HEMW R 2	18	6.5	12	300	FPM
HEMW R 3	34	6.5	12	300	NBR
HEMW R 4	34	6.5	12	300	FPM




HEMW V

Type	H	S	T	W	Length	Material
HEMW V 1	21	20	11	6	560	NBR
HEMW V 2	21	20	11	6	560	FPM
HEMW V 3	26	25	11	6	560	NBR
HEMW V 4	26	25	11	6	560	FPM
HEMW V 5	26	25	11	6	1000	NBR
HEMW V 6	26	25	11	6	1000	FPM



HEMW K

Type	H	S	T	W	Length	Material
HEMW K 1	18	15	7.5	4.5	500	NBR
HEMW K 2	18	15	7.5	4.5	500	FPM
HEMW K 3	25	22	7.5	4.5	500	NBR
HEMW K 4	25	22	7.5	4.5	500	FPM




MOLDED WIPERS

All dimensions shown in mm.


HEMW P

Type	H	T	W	Length	Material
HEMW P 1	30	9.5	3	1000	NBR
HEMW P 2	30	9.5	3	1000	FPM




HEMW S

Type	H	S	T	W	Length	Material
HEMW S 1	18	11.5	6	2.6	300	NBR
HEMW S 2	18	11.5	6	2.6	300	FPM
HEMW S 3	25	18.5	6	2.6	300	NBR
HEMW S 4	25	18.5	6	2.6	300	FPM
HEMW S 5	30	23.5	6	2.6	300	NBR
HEMW S 6	30	23.5	6	2.6	300	FPM
HEMW S 7	40	33.5	6	2.6	300	NBR
HEMW S 8	40	33.5	6	2.6	300	FPM



HEMW N


Type	H	E	T	W	Length	Material
HEMW N 1	26	10	9	3	500	NBR
HEMW N 2	26	10	9	3	500	FPM
HEMW N 3	26	10	9	3	1000	NBR
HEMW N 4	26	10	9	3	1000	FPM



HEMW U 1/2

Type	H	S	T	W	Length	Material
HEMW U 1	25.4	22	12.7	6.35	560	NBR
HEMW U 2	25.4	22	12.7	6.35	560	FPM

Classic design with steel support




MOLDED WIPERS

All dimensions shown in mm.

HEMW U 3/4

Type	H	S	T	W	Length	Material
HEMW U 3	25.4	22	12.7	6.35	560	NBR
HEMW U 4	25.4	22	12.7	6.35	560	FPM


Flexible design without steel support



HEMW U 5/6


Type	H	S	T	W	Length	Material
HEMW U 5	25.4	22	12.7	6.35	560	NBR
HEMW U 6	25.4	22	12.7	6.35	560	FPM

Flexible design with spring steel strip




HEMW U 7/8

Type	H	S	T	W	Length	Material
HEMW U 7	25	21	11	6	560	NBR
HEMW U 8	25	21	11	6	560	FPM



HEMW U 9/10

Type	H	S	T	W	Length	Material
HEMW U 9	25	21	11	6	560	NBR
HEMW U 10	25	21	11	6	560	FPM




MOLDED WIPERS

All dimensions shown in mm.

HEMW U 11/12


Type	H	S	T	W	A	B	Material
HEMW U 3	25.4	22	12.7	6.35	76.2	76.2	NBR
HEMW U 4	25.4	22	12.7	6.35	76.2	76.2	FPM

elbow




HEMW X1/2

Type	H	S	T	W	Length	Material
HEMW X 1	27.5	21.5	10	6	500	NBR
HEMW X 2	27.5	21.5	10	6	500	FPM




HEMW X3/4

Type	H	S	T	W	U	Length	Material
HEMW X 3	27.5	21.5	10	6	25.2	500	NBR
HEMW X 4	27.5	21.5	10	6	25.2	500	FPM



SK

- High molding accuracy ensures excellent wiping results.
- The wipers consist of synthetic rubber vulcanized on a steel plate.
- Lip materials: NBR, silicone and NBR, silicone and FPM.
- Support profile materials: Steel (also galvanized), high-grade steel or aluminum.
- Permanent temperature resistance 100°C, momentarily 135°C.
- Resistant to mineral oil, coolants, and micro-organisms.
- High dimensional accuracy.
- Good resistance to abrasion.
- Little deformation by compression.




AL (ALUMINUM ENCASED)


- Particularly suitable in case of high volumes of coolants and swarf.
- Easy to cut and process, these wipers are ideal for service and repair.
- Anodized aluminum precision profile with integrated lip protection against hot swarf.
- Replaceable lip.
- The two-way wiper system prevents the penetration of swarf and coolant.
- Fastening with hexagon socket screws according to DIN 912, oval head or button head socket screw.
- The 90° connecting pieces ensure the connection of the wiper sides.

All dimensions shown in mm.

AL1




AL3



AB I, III, IV (STEEL ENCASED)

- For use in metal-cutting machines with large volumes of chips and coolants.
- Standard lengths can be profiled by the customer for service and repairs.
- Factory-profiled forms ensure an excellent wiping performance.
- Stainless steel support profiles ensure high mechanical stability under permanent load.
- With elastic, highly abrasion-proof polyurethane wiper lips. Permanent temperature resistance 90°C.
- Partly resistant to acids, leaches, and gasoline.
- Easy to replace.
- The miter joints of the wiper casing are welded.
- 90° wiper lip with a 45° chamfer molded in one piece.
- Protected against hot chips and mechanical damage.
- Standard lengths available in stock (mm): AB I, AB III - 530/1000/2000, AB V - 1000
- Can be profiled to nearly any designs according to drawing or sketch.
- Mounting holes included upon request.


All dimensions shown in mm.



C-SERIES, eN, F (WAY COVER WIPERS)



■ wiper lip
 ■ profile support
 ▨ sheet metal box
 ■ damping material
 ■ profile support

All dimensions shown in mm.





C SERIES

- Same design for all types of C wipers (except CL1—see below)
 - Highly wear-resistant polyurethane lips ensuring optimum resistance to water, coolants, chemicals and oil
- See page 11 for variations and dimensions**





C SERIES - CL1

- Usable for large surfaces and aluminum apron systems for manifold applications
- Optimum wiping effect: will wipe uneven surfaces up to 4 mm
- Highly durable and resistant against all common coolants
- Exchangeable and suitable for all profiles of series C2, C3, C5, and C6 profiles from the C Series (Illustration: CL1 with C2 profile)




eN SERIES

- Used on telescopic steel way covers for slideways with small cross-sections
- Wiper lip vulcanized to a flat steel profile
- Highly wear-resistant polyurethane lip, resistant to oil, coolants, and microbes
- Standard length: 500 mm



F (mini)


- Compact wiper with a height of only 11.5 mm
- Especially useful where space is limited, e.g. on extractors or slides
- The wiper lip is vulcanized on a steel profile
- Low priced wiper based on the proven SK-series
- Standard length: 500 mm



C-SERIES (WAY COVER WIPERS)



■ wiper lip
 ■ profile support
 ▨ sheet metal box
 ■ damping material
 ■ profile support

All dimensions shown in mm.





C2

- Smallest wiper of the "C" series
- Replaceable wiper lips
- Very little space required (regarding the mounting height and depth)
- Also available with a rubber profile vulcanized on the profiled support, for optimum damping properties at high traverse speeds (illustrations show C2 with damping)





C3

- Wider profile to ensure a better adhesion when spot-welding it to the box
- Replaceable wiper lips
- Mounting height requires very little spacing
- Can be screwed onto the cover box
- Optimum rigidity of the cover box in the wiper area
- Available with and without damping (illustration to the left shows wiper without damping, illustration to the right shows wiper with damping)
- Assembly dimension with damping 18 mm




C5

- Designed for large covers
- Replaceable wiper lips
- A combination of C5 and C3 wipers is possible
- Optimum rigidity of the cover box in the wiper area
- Enlarged return gutter to ensure a rapid draining of the coolant
- Available with and without damping (illustrations show C5 with damping)



C6

- Can be replaced directly on the machine without disassembling the cover
- Time saving and cost-effective
- Enlarged return gutter to ensure a rapid draining of the coolant
- Available with and without damping (illustrations show C6 with damping)
- Replaceable profile (shown in blue) is fixed with spring clamps
- Solid profile support (shown in red) is welded with the box plate and remains on the cover



FACILITIES & CONTACTS



- Headquarters / Manufacturing / Distribution / Service Center
- Manufacturing / Distribution / Service Center
- Manufacturing / Distribution
- Sales Partner
- Service Center

1 Hennig, Inc. Global Headquarters

9900 North Alpine Road
Machesney Park, IL 61115
T: +1 815-636-9900
F: +1 815-636-1988
info@hennig-inc.com

4 Cobsen Ltda.

R. Benedito Mazulquim, 425
18550-000 Boituva CEP, Brazil
T: +55 15 3263-4042
F: +55 15 3263-4070
cobsen@cobsen.com.br

7 Hennig France sas

19, rue de Rebrillon
03300 Creuzier-le-Neuf, France
T: +33 470 58 4740
F: +33 470 58 0022
contact@hennig-france.com

2 Hennig, Inc. Oklahoma Service Center

900395 S. 3420 Road
Chandler, OK 74834
T: +1 405-258-6702
F: +1 405-258-9971
info@hennig-inc.com

5 Hennig GmbH European Headquarters

Überrheinerstraße 5
85551 Kirchheim, Germany
T: +49 89 96096-0
F: +49 89 96096-120
info@hennig-gmbh.de

8 Hennig U.K. Ltd.

Unit 6, Challenge Close
Coventry CV1 5JG, United Kingdom
T: +44 24 76555690
F: +44 24 76256591
sales@henniguk.com

3 Hennig, Inc. Michigan Service Center

11879 Brookfield Road
Livonia, MI 48150
T: +1 734-523-8274
F: +1 855-427-1549
info@hennig-inc.com

6 Hennig CZ s.r.o.

Klánovická 334
250 82 Úvaly, Czech Republic
T: +420 2810 91610
F: +420 2810 91625
info@hennig-cz.com

9 Hennig BH doo.

Ciljuge II bb – poslovna zona
75270 Zivinice, Bosnia Herzegovina
T: +387 35 95 1876
kontakt@hennig-bh.com



10 BB & S Industrieel Onderhoud
Zirkoonstraat 7, 7554 TT Hengelo (Ov.)
Postbus 69
7550 AB Hengelo (Ov.), Netherlands
T: +31 74 8510600
F: +31 74 8510605
hinders@bs.nl

11 Svenska Maskinkomponenter AB
Brunnsäkersvägen 9
64593 Strängnäs, Sweden
T: +46 8 53470770
F: +46 8 53470775
info@svemako.se

12 Hennig Portugal Unipessoal Lda
Rua de Lages 386
4575-300 Paredes-Penafiel, Portugal
T: +49 172 6429207
a.dasilvaduarte@hennig-gmbh.de

13 Osung Mechatronics Co. Ltd.
Jinbuk-myun Shincon-li 413-2
Gyungnam Masan-city, South Korea
T: +82 55 271 1821
F: +82 55 271 1820
osgijeon@naver.com

14 Enomoto BeA Co., Ltd.
5-10 Sohara Koa-Cho
Kakamigahara-Shi,
Gifu 504-8551, Japan
T: +81 583 832178
F: +81 583 897435
kashida@enomotoweb.com

The background of the advertisement features a dark blue gradient with several large, semi-transparent images of industrial machinery components. On the left, there are two large circular parts, possibly flanges or end plates, with various bolt holes and a central cutout. On the right, there are several rectangular and L-shaped components, likely structural frames or supports, with some featuring circular openings. The overall aesthetic is industrial and professional.

|||| HENNIG®

PROTECT YOUR SUCCESS

WE'VE GOT YOUR BACK

We help create and maintain a safe and efficient workplace for manufacturers, safety facilities, stand-by power systems, and maintenance facilities around the globe. Since 1950, Hennig Worldwide has been defining excellence in chip management, machine protection and facility safety, creating regional jobs, serving their local communities, and supporting the global needs of machine tool customers.

**ISO 9001:2015
REGISTERED**

9900 North Alpine Road
Machesney Park, IL 61115
815.636.9900

hennigworldwide.com

WS_0626